



## **Pittasoft Co., Ltd.**

IP Network Cameras; Network Video Recorders; Web Interface

### **Main Contacts:**

LPR Global, Inc.

[www.uskoreahotlink.com](http://www.uskoreahotlink.com)

416-423-5590

[info@lprglobal.com](mailto:info@lprglobal.com)

### **Corporate Overview**

Pittasoft Co., Ltd, is a Korea-based manufacturer of next generation H.264-based IP Network Cameras covering all security surveillance needs. Pittasoft's new IP Network Camera Lineup for 2009 includes Pitta 300 and Pitta 300R. These color IP Network Cameras are ideal for applications ranging from surveillance to remote monitoring in areas such as shopping malls, airports, warehouses and more. The Pitta 300 and Pitta 300R IP Network Cameras are flexible and adaptable, enabling a greater range of applications. These cameras can be quickly mounted using the simple bracket assemble that comes with each camera.

The Pitta 300 and Pitta 300R use a superior CMOS Sensor that delivers crystal clear images. The CMOS sensor is also extremely light sensitivity, so that video can be captured even in very low light environments or during "near dark" times of the day. The Pitta 300 and Pitta 300R support H.264 and JPEG compression. H.264 Codec uses a bandwidth efficient, high quality video compression technology and is optimal for real-time viewing of video. The Pitta 300 and Pitta 300R can be connected, controlled and monitored from a remote location through an internet or intranet IP connection. Many Pittasoft customers find it easier to install Pitta 300 and Pitta 300R than CCTV and DVR systems owing to its state-of-the-art embedded technologies.



## Pittasoft Product Highlights

### Pitta 300 and Pitta 300R IP Network Camera

- Industry Standard H.264-based real-time live video streaming
- VGA CMOS image sensor for crystal clear images
- Supports H.264 and JPEG Compression
- Multi-view video management software for up to 16 cameras
- Integrated motion detection with e-mail and FTP upload for still images and videos
- Supports H.264 video streaming with Constant and Variable Bit Rate
- Up to 30 Frames encoding @ VGA (640x480)
- Provide Windows-based Camera installer and Easy Firmware Update Through Network
- Integrated E-mail, FTP, DDNS, and DHCP client
- Linux Based Operation System
- Fast Ethernet Connectivity

### Pitta WebView – Viewing over the Web

- LiveView – View, snapshot and record functionalities
- Setup - Easy Configuration for regular users. Advance settings option for power-users
- User list – Programmable User list for video viewing and / or for camera control functions
- Logon Authentication – 4 to 32 characters username and 4 to 10 character password
- Users - -Maximum 1 admin and 6 viewers configuration
- Video resolution – 640 x480; 352x288; 320x240; 176x144
- Codec supported – H.264
- JPEG Configurations – Configurable compression ratio
- Event Configuration – Motion detection

### Pitta View – Network Video Recorder

- Remote Operations – Live View and Playback
- Views layout – 1x1; 2x2; 3x3; 4x4; 1Px7; 1Px12 layouts and full screen.
- Alerting – notify users on event or motion detected
- Camera searching
- Complete systems management
- Stores users actions by time, location of motion detection and full system operation MP4 file format

